AQ 191 F Page 1 OF 5 Date:00/09 Appr: H.D.M.

| SECTION 1 : PRODUCT INFORMATION | | | | | | |
|--|---|---------|--|--|------------------|--|
| PRODUCT: SCREWS FINISHING COMPOUND USAGE : FLEXIBLE PROTECTIVE AND WATERPROOFING SLURRY SEAL | | | | | Part A | |
| MANUFACTURER: FINEX INC. 110 boulevard Bord de l'Eau Valleyfield, Qc, J6S 4V3 | | | | | | |
| EMERGENCY TELEPH | EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666 | | | | | |
| TDG Classification UN Number Packaging Group | Not regulated Not established Not applicable | | WHMIS Classification Class: | Not regulated Not applicable | | |
| | SECTION | I : HAZ | ARDOUS INGREDIENTS | | | |
| | | | | LD₅₀ (mg/kg) | LC ₅₀ | |
| Hazardous ingredients | % | T.L.V. | #Cas | (species, route) | (species, route) | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | SECTION III | : PHYS | ICAL CHARACTERISTICS | | | |
| | | | | | | |
| Physical State Appearance and odor Odor Threshold Evaporation rate Vapor density Vapor pressure | :Liquid :Milky Liquid, Acrylic odor :Not established :<1 (water) :<1 (water) :17 mm (20°C) | | Boiling point Freezing point Density Water solubility PH % volatility Water/oil distribution | :100°C :0°C :1,02 :Yes :8-10 :70-80 :Not established | | |
| | | | | | | |

AQ 191 F Page 2 of 5 Date:00/09 Appr: H.D.M.

| PRODUCT: SCREWS | FINISHING COMPOUND | | | Part A |
|---|---------------------------------|---|---------------------------------|--------|
| SECTION IV :FIRE AND EXPLOSION HAZARDS | | | | |
| SECTION IV :FIRE AND EXPLOSION HAZARDS | | | | |
| Inflammability If yes, under what Extinguishing methods | :No : :Foam, dry chemical | TDG inflammability Class Flammable under limits (%vol) Flammable lower limits (%vol) Flash point (method used) | | |
| | | Auto-ignition temperature Dangerous combustion produc | | |
| Special methods | :Firefighters must wear | Protect from mechanical impa :No | | |
| | | Protect from static discharge | :No | |
| | | | | |
| | | REACTIVITY DATA | | |
| | SECTION | | | |
| Chemical stability | :Yes | Dangerous decomposition | :Carbon oxides acrylic monomer. | |
| If not, under what | :But excessive heat can | | | |
| | | Polymerisation risks | :No | |
| Incompatibility with | :No | | | |
| If yes, which ones | : | | | |
| | | | | |
| | | | | |
| | | | | |

AQ 191 F Page 3 of 5 Date:00/09 Appr: H.D.M.

| PRODUCT: SCREWS FINISHING COMPOUND | | | Part A |
|------------------------------------|--------------------------------------|-------------------------------|-------------------------------------|
| SECTION VI : TOXIC PROPERTIES | | | |
| ROUTE OF ENTRY / C | CONTACT | | |
| Eyes | :May cause eye irritation. | Ingestion | :May cause |
| Skin | :May cause skin irritation. | Carcinogenicity | :No |
| Inhalation | :May cause irritation to lungs. | Toxic effects on reproduction | :No |
| | | Teratogenicity | :No |
| | | Mutagenicity | :No |
| | | Product with synergistic | :Not established |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| An acute or chronic ex problems. | posure will increase the toxicologic | problems mentioned in this se | ction and may aggravate respiratory |

AQ 191 F Page 4 of 5 Date:00/09 Appr: H.D.M.

| PRODUCT: SCREWS | FINISHING COMPOUND | | Part A |
|---------------------------------|----------------------------------|-------------------------------|-------------------------|
| | SECTION VII : P | REVENTIVE MEASURES | |
| INDIVIDUAL EQUIPMENT PROTECTION | | | |
| Gloves | :Chemical resistant gloves. | Handling and Equipment | :Avoid skin, eye |
| Respiratory equipment | :Not necessary. | | |
| Eyes | :Safety glasses | Warehouse requirements | :Keep all |
| Shoes | :Ordinary | | |
| Clothing | :Rubber apron | Special shipping instructions | :Protect from freezing. |
| Other | :No | | |
| Ventilation: | :Sufficient ventilation required | | |
| Procedure in case of | :Absorb with sand or other | Residue eliminations | Dispose of sand |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

AQ 191 F Page 5 of 5 Date:00/09 Appr: H.D.M.

| PRODUCT: SCRE | WS FINISHING COMPOUND | Part A |
|-------------------------------------|---|--------|
| | | |
| | SECTION VIII : FIRST AID | |
| Skin | Remove and clean contaminated clothes. Wash with plenty of soap and water the exposed areas. Consult with a physician if necessary. | |
| Eyes | :Clean with water for at least 15 minutes Consult with a physician if necessary | |
| Inhalation | In the case of overexposure, evacuate to fresh air. Consult a physician if necessary | |
| Ingestion | :Do not induce vomiting. Drink plenty of water. Consult a physician . Do not give anything by mouth to an unconscious person. | |
| | SECTION IX : PREPARATION INFORMATION | |
| Prepared by Telephone # Fax # | :Helios D. Muñoz :(450)373-0909 :(450)377-0440 | |